

Document made available under the Patent Cooperation Treaty (PCT)

International application number: PCT/GB05/000816

International filing date: 03 March 2005 (03.03.2005)

Document type: Certified copy of priority document

Document details: Country/Office: GB
Number: 0404961.5
Filing date: 04 March 2004 (04.03.2004)

Date of receipt at the International Bureau: 21 April 2005 (21.04.2005)

Remark: Priority document submitted or transmitted to the International Bureau in compliance with Rule 17.1(a) or (b)



World Intellectual Property Organization (WIPO) - Geneva, Switzerland
Organisation Mondiale de la Propriété Intellectuelle (OMPI) - Genève, Suisse



GB05/816



INVESTOR IN PEOPLE

The Patent Office
 Concept House
 Cardiff Road
 Newport
 South Wales
 NP10 8QQ


I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

I also certify that the application is now proceeding in the name as identified herein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.



Signed

Dated 5 April 2005



GB 0404961.5

By virtue of a direction given under Section 30 of the Patents Act 1977, the application is proceeding in the name of:

INOVA DESIGN LTD.,
Catherine's Field,
The Spinning Walk,
SHERE,
Surrey,
GU5 9HN,
United Kingdom

Incorporated in the United Kingdom,

[ADP No. 08911414001]

Pat 1977
(Rule 1)

**THE
Patent
Office**

05MAR04 E878501-5 D02136
P01/7790 0.00-0404961.5 CHEQUE

Request for grant of a patent

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)



The Patent Office

Cardiff Road
Newport
Gwent NP9 1RH

1.	Your reference	JE/N15275		
2.	Patent application number (The Patent Office will fill this part)	04 MAR 2004	0404961.5	
3.	Full name, address and postcode of the or of each applicant (underline all surnames)	Leon Thomas Lee <u>Marsh</u> Catherine's Field The Spinning Walk Shere Surrey GU5 9HN		
	Patents ADP number (if you know it)	SECTION 30 (1977 ACT) APPLICATION FILED 15/7/04		
	If the applicant is a corporate body, give the country/state of its incorporation	8722132001		
4.	Title of the invention	HYDRATION MONITOR		
5.	Name of your agent (if you have one)	Williams Powell		
	"Address for service" in the United Kingdom to which all correspondence should be sent (including the postcode)	Morley House 26-30 Holborn Viaduct London EC1A 2BP United Kingdom		
	Patents ADP number (if you know it)	830310001		
6.	If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (if you know it) the or each application number	Country	Priority application number (if you know it)	Date of filing (day / month / year)
7.	If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application.	Number of earlier application	Date of filing (day / month / year)	
8.	Is a statement of inventorship and of right to grant of a patent required in support of this request? (answer 'Yes if: a) any applicant named in part 3 is not an inventor, or b) there is an inventor who is not named as an applicant, or c) any named applicant is a corporate body	No		

9. Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document

Continuation sheets of this form

Description	13
Claim(s)	3
Abstract	1
Drawing(s)	2

10. If you are filing one of the following, state how many against each item.

Priority documents

Translations of priority documents

Statement of inventorship and right to grant of a patent (*Patents Form 7/77*)

Request for preliminary examination and search (*Patents Form 9/77*)

Request for substantive examination (*Patents Form 10/77*)

Any other documents
(please specify)

11. I/we request the grant of a patent on the basis of this application.

Signature

Date

4 March, 2004

12. Name and daytime telephone number of person to contact in the United Kingdom

Mr Lee Anderson 020 7936 3300

Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 0645 500505.
- Write your answers in capital letters using black ink or you may type them.
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- If you have answered 'Yes' Patents Form 7/77 will need to be filed.
- Once you have filled in the form you must remember to sign and date it.
- For details of the fee and ways to pay please contact the Patent Office.

Patents Form 1/77




Figure 1




Figure 2

2/2




Figure 3




Figure 4

HYDRATION MONITOR

DUPLICATE

Field of the Invention

The present invention relates to a hydration monitor and in particular to a portable

5 hydration monitor suitable for use during exercise.

Background to the Invention

10 In sport, particularly athletics, international competition is the ultimate challenge to the various regulatory systems of the body: physiological; biochemical; biomechanical and psychological. The body experiences a great challenge to accommodate the metabolic, thermal and other demands of intense exercise, where this challenge is greatest during endurance events in hot environments.

15 Since water serves the role of controlling most of the body's regulatory systems, the need for fluid intake during exercise is one of the main concerns, if not the primary concern, for the sportsperson in ensuring they can maintain their maximum sporting potential. The body's management of its *hydration* status is essential in its main roles of regulating body temperature; blood circulation, volume, viscosity and pressure; facilitating muscle movement and for removing
20 waste.

A deficient level of hydration can lead to dehydration; a process referring to a loss of body water, from a state of hyperhydration (greater than normal body water content) to euhydration (normal body water content) or from euhydration
25 downward to hypohydration (less than normal body water content).

In terms of performance, a subject who is just 2% dehydrated can see their performance drop by 20-30%, when compared to being in a state of euhydration. Put in context, this reduction in performance compares to the margin between
30 winning gold and finishing outside of the medals, 7 seconds adrift, in the 1500m in the 2000 Sydney Olympics.

It is important, however, to emphasise that hydration is not the only factor that should be monitored in exercise. Other factors such as energy stores, levels of

electrolytes, fatigue, psychological factors and fitness (reduced fitness in elite athletes is due to insufficient recovery time to regain fitness after sustaining an injury) all have an effect on the performance of the sportsperson, and since the nature of sport is based around precision, an imbalance of any of these factors can lead to underachievement. In extreme cases, it has been known for a deficiency of electrolytes to be fatal, inducing a condition known as hyponatremia. The condition is often brought on through the dilution of sodium content in the blood, where the subject has consumed too much fluid without an adequate replacement of sodium.

It is the occasion where an athlete has the perfect balance of the above factors that they will perform at their lifetime best. A performance such as this requires the mind of the athlete to be in harmony with their body, an occurrence known simply as 'the zone'. It is an altered state of consciousness where the body and mind function automatically.

It is therefore desirable to be able to monitor hydration levels to achieve maximum possible performance. It is particularly desirable to be able to measure hydration levels during exercise to determine the quantity of liquid that should be taken on board to maintain, or reach, ideal hydration levels.

Current systems used for measuring hydration include osmometers and refractometers. Such systems are used by sporting bodies and clubs, although due to the size of the apparatus involved and the nature of the measurements taken, the systems can only be used before, during a stationary phase, or after an exercise is finished.

Osmometers work on the principle of either freezing point depression or vapour pressure (heating and cooling). Osmometers determine the number of water particles in a blood solution obtained from a subject by taking a blood sample. Another form of osmometry measures the concentration of water in a urine sample. In both cases, osmometry is not practical for use during exercise due to the need to collect blood or urine samples.

Refractometers measure the specific gravity of urine samples. By placing a drop of urine on the screen, the concentration of the urine is read off from a scale, the reading being determined by the refraction of light through the urine. The reading on the scale can then be converted into a number of milli-osmos per Kilogram.

5 Again, it is not practical for use during exercise due to the need of a urine sample.

Although portable skin hydration monitors exist, such devices are designed for use in dermatology as a measure for skin moisture. Skin hydration monitors measure moisture levels in the corneocytes (dead skin cells) in the stratum corneum, the
10 outer layers of the skin. In terms of body water, a normal moisture level in the stratum corneum could either be the result of, firstly, body euhydration or, secondly, sweating whilst in a dehydrated state. It therefore follows that skin hydration levels do not reflect body hydration. It is also not possible to determine the level and quantity of sweat, since the water in the stratum corneum reaches a
15 maximum when the body is in a state of euhydration. Therefore it would not be possible to determine any excess sweat that evaporates or drips off the skin.

It has been suggested that blood flow monitors could be adapted to determine fluid status, through monitoring how peripheral blood flow varies during exercise to
20 facilitate the dissipation of heat by the process of sweat and heat exchange. However, it is thought that this would not be a reliable method of monitoring hydration because sweat rates, and therefore blood flow rates, are greater in hot than in cold climates, even for the same level of dehydration. Peripheral blood flow fails to allow for other means of losing fluid such as increased fluid exchange
25 in cold climates between the environment and breath, where the environment draws moisture from the breath to try and equalise the two moisture levels.

It is understood from medical studies that for every 1% loss in body weight, due to dehydration, heart rates increase by about 7 beats per minute. From this, it may
30 be possible to develop a heart rate monitor to calculate loss in hydration due to an increase in heart rate. However, it is not thought that such a monitor would be particularly accurate as heart rate increases could also be the result of other factors. For example, an increase in speed from one stride to the next would

cause an increase in heart rate, as would anxiety, hormone levels, caffeine intake and the (varying) temperature of the atmosphere.

Bio-electrical Impedance Analysis (BIA) is another technique that has been suggested for use in measuring hydration. BIA analyses the amounts of fat, muscle and water in the body. The measure of hydration is separated into intracellular and extra cellular fluid compartments. BIA works by sending a small current through electrodes attached to the skin, normally on the hand and the foot. The current is sent at two different levels, one that can penetrate the cells of the body and one that cannot. The difference between the two provides an indication of the hydration status, on the theory that fluid facilitates the conduction of current. Currently, BIA results are affected by numerous variables including body position; hydration status; consumption of food and beverages; ambient air and skin temperature; recent physical activity; and the conductance of anything in contact with the skin, other than the electrodes. Thus, BIA lacks the precision and accuracy necessary for hydration monitoring, and it is doubtful that it could ever be adapted for use to determine fluid levels during even gentle exercise.

The present invention seeks to provide means for monitoring hydration in the body during exercise. It was therefore important to understand whether or not the theories behind any existing products could be developed for use in the PHM.

Statement of Invention

According to an aspect of the present invention, there is provided a hydration monitor comprising a temperature sensor for measuring a subject's core body temperature and a processor, the processor being arranged to accept measurements from the temperature sensor and calculate a hydration level in dependence on changes in the measured core body temperature.

In a preferred embodiment of the present invention, a portable monitor is arranged to measure core body temperature non-invasively. Hydration is monitored in real-time device and measurements are output via a display to the user. In this manner, a user can see his or her hydration status during exercise. Through this, it is intended that dehydration is avoided and thus performance maximised.

The portable hydration monitor is particularly useful as it can be used to analyse an athlete's performance to ensure their maximum sporting potential and it can be used to guarantee that the level of hydration is always safe. Thus, severe dehydration can be avoided, something that can ultimately be a risk to health and even survival.

Many internal and external variables (including psychological variables) are relative to the core body temperature that is measured. In particular, by use of a hydration monitor according to an embodiment of the present invention, stitch and stomach discomfort should be prevented.

Embodiments of the present invention could be used by almost all sportsmen/women including the disabled. Embodiments of the present invention could be produced specifically for impact sports. In particular, the earpiece or other temperature sensor would be designed so it could not be damaged by impact or be forced into the ear by jostling/impact.

Preferably, the temperature sensor includes one or more air flow channels allowing the flow of ambient air around the ear canal. Preferably, the temperature sensor is designed to stably fit within the subject's ear and maintain a constant position. For example, the temperature sensor may be mounted within a malleable rubber member or similar to allow it to adaptably fit within different sized ears of subjects. In another alternative, various sized ear pieces may be provided to permit a subject to select the most appropriate fit.

In a preferred embodiment, the portable hydration monitor includes an earpiece containing a thermopile to measure core body temperature via the tympanic membrane (eardrum) and a wristwatch or other visual and/or audible indicator module that provides the user with real-time feedback and informs the user of how much fluid they must drink to re-hydrate their body to a level of euhydration (normal).

Preferably, the two units communicate wirelessly.

The thermopile detects incident infrared radiation from the tympanic membrane and provides a voltage equivalent to the core body temperature of the subject. This is then fed into an algorithm and the result is output via the indicator module.

- 5 Preferably, the result is the volume of fluid the subject should consume, in litres or ml to reach and/or maintain a level of euhydration.

Preferably, the monitor seeks to provide the athlete with a realistic accuracy of 0.5-1.0 %BWL (body weight lost in water).

10

This present invention seeks to provide a portable hydration monitor suitable for monitoring hydration status throughout an exercise, which in turn would educate athletes during training so that the regular and appropriate intake of fluids is automatic, and in competition they can concentrate solely on performing in 'the zone' (they may not be wearing the device during competition).

15

Various embodiments may eventually be produced to cater for the various needs of:

- athletes (and novice sports person);
- 20 • military personnel;
- hospital patients and
- normal public users

20

The hydration monitor may comprise an earpiece and a remote unit, the temperature sensor being positioned in the earpiece for measuring the core body temperature via the subject's tympanic membrane.

25

Preferably, the temperature sensor comprises a thermopile.

- 30 The earpiece may further comprises a transmitter, the remote unit including the processor, output means and a receiver, the earpiece being arranged to communicate measurements to the processor via the transmitter and receiver, the processor being arranged to provide an indication of the hydration level via the output means.

The transmitter and receiver may communicate wirelessly.

The transmitter and receiver may be transceivers.

5

The remote unit may comprise a selected one of:

a wristwatch, a personal digital organiser, a mobile telephone, a personal computer or medical diagnostic and/or monitoring apparatus.

- 10 The output means may include one or more of a display and a speaker.

The monitor may further comprise a memory for storing hydration level and/or core body temperature over time.

- 15 The processor may be arranged to determine a hydration level by the following formula:

$$[(\text{core body temperature current} - \text{core body temperature normal}) \times \text{subject's weight}] / (\text{factor of ambient compensation} \times 100).$$

- 20 The factor of ambient compensation may be between 0.1 and 0.23 and is determined in dependence on the temperature of the environment surrounding the subject.

- 25 The hydration monitor may be arranged to operate repeatedly at predetermined time intervals.

The processor may be arranged to generate an alarm upon determination of a hydration level below a predetermined level.

- 30 According to another aspect of the present invention, there is provided a method of measuring hydration of a subject comprising the steps of:

measuring an initial core body temperature of the subject;

measuring a subsequent current core body temperature of the subject;

subtracting the initial core body temperature from the subsequent core body temperature;

multiplying by the subject's weight; and,
dividing by a factor of ambient compensation.

Preferably, the measurements are taken from the subject's tympanic membrane.

Brief Description of the Drawings

Embodiments of the present invention will now be described in detail, by way of example only with reference to the accompanying Figures, in which:

Figure 1 is a block diagram of a hydration monitoring system according to an embodiment of the present invention;

Figure 2 is a schematic diagram of a portable hydration monitor incorporating the system of Figure 1;

Figure 3 is a cross-sectional diagram of an earpiece of the monitor of Figure 2;
and,

Figure 4 is a schematic diagram of another system according to an embodiment of the present invention.

Detailed Description

Figure 1 is a block diagram of a hydration monitoring system according to an embodiment of the present invention.

The hydration monitoring system 10 includes a temperature sensor 20, a processor 30 and a display 40.

The temperature sensor 20 is arranged to measure body temperature of a subject and communicate the measured temperature to the processor 30. Upon receipt of the measurement, the processor is arranged to calculate a body water level for the subject and output a corresponding hydration indication to the display 40.

Preferably, the temperature sensor 20 is arranged to measure temperature of a tympanic membrane within one of the subject's ears.

The calculation performed by the processor is carried out at regular intervals as follows:

$$\frac{[(\text{core body temperature current} - \text{core body temperature normal}) \times \text{weight}]}{(\text{factor of ambient compensation} \times 100)}$$

The normal core body temperature will have been determined and/or input into the device prior to use. The normal core body temperature is subtracted from the current core body temperature, multiplied by the weight of the subject in kg, (although could also be configured to accept pounds depending on user's preference) and then divided by the factor of ambient compensation. This is then either divided by one hundred to give a measurement in litres or alternatively multiplied by ten to give the measurement in millilitres.

The factor of ambient compensation is valued between 0.1 and 0.23 degrees centigrade, and refers to the increase in the subject's core body temperature for every percent loss of body weight, in temperate and hot climates respectively.

The measurement is the amount of liquid that the subject should drink to achieve euhydration (full hydration).

Figure 2 is a schematic diagram of a portable hydration monitor incorporating the system of Figure 1. Figure 3 is a cross-sectional diagram of an earpiece of the monitor of Figure 2.

The portable hydration monitor includes an earpiece 60 and a wristwatch 70.

The earpiece 60 includes a thermopile 65 positioned to measure core body temperature via the tympanic membrane when inserted into an ear of a subject and a transmitter 66 arranged to communicate temperature measurements to the wristwatch 70.

The transmitter and receiver could be transceivers to allow the two units to talk to each other for initialisation etc.

The wristwatch 70 includes a receiver 75 arranged to receive measurements from the earpiece, a processor to perform the calculations discussed above and a display 76 to provide the subject with feedback on their hydration status.

- 5 Preferably, the display also informs the user of how much fluid they must drink to re-hydrate their body to a level of euhydration (normal). Preferably, the monitor operates on a substantially real-time basis.

- 10 In addition or as an alternative to the display 76, the wristwatch 70 may include an audible indicator 80 to provide the feedback and/or additional alerts. For example, hydration status and feedback may be provided via the display 76 and alerts may be provided via the audible indicator 80 when a predetermined level of dehydration is reached and/or immediate action is necessary.

- 15 Preferably, the transmitter 66 and receiver 75 communicate via a wireless data protocol such as Bluetooth™ or another suitable wireless communication system. The earpiece 60 and wristwatch 70 both include one or more batteries to supply power. At least in the case of the earpiece 60, it is preferred that the battery 67 is rechargeable from within the earpiece via a suitable connection to a power-source or inductive coupling to a power-source. In order to conserve battery power, the
- 20 transmitter 66 may establish a connection with the receiver only when it is provided with data to transmit. The earpiece 60 and/or wristwatch may include a sleep mode to further conserve power when not in use.

- 25 When inserted into a subject's ear canal, the thermopile 65 detects incident infrared radiation from the tympanic membrane and provides a voltage equivalent to the core body temperature of the subject. This is transmitted to the wristwatch and used by the processor to obtain a hydration indication for output via the display and/or audible indicator. Preferably, the result is the volume of fluid the
- 30 subject should consume, in litres or ml.

Preferably, the wristwatch includes a memory and is connectable to a computer or other remote station, either via a wireless connection or via a docking station or other wired connection to enable the subject to store and subsequently download

core body temperature and/or hydration statistics and other relevant information for subsequent analysis.

If configured by the user, an alert can be set to sound periodically (for example, every minute) to indicate when the temperature is measured. The alert will preferably be generated in the earpiece but it could alternatively be generated from the wristwatch, or both. The alert is intended to remind the subject to look at the display and could also serve to indicate when the display is being updated. If ignored, and the subject becomes dehydrated, the device will sound an alarm, either in the earpiece or wristwatch or both when their hydration status falls below 2% of their level of euhydration.

Depending on the configuration of the wristwatch and earpiece, the user may be given a choice of a sound or vibration alert, or both.

It is understood from medical studies that for every 1% loss in body weight, due to dehydration, heart rates increase by about 7 beats per minute. From this, it may be possible to incorporate a heart monitor into embodiments of the present invention to provide more detailed information on hydration status. The heart rate monitor would be one of the many types currently available and would be arranged to communicate its measurements with the wristwatch in the same manner as the earpiece.

In addition, pressure detecting inserts could be included in an embodiment of the present invention. Such inserts would be inserted into shoes and arranged to measure weight by the pressure applied. This information could then be communicated to the wristwatch which could calculate a weight change due to fluid loss. This method is expected to be unreliable by itself as it is affected by balance distribution over the foot, for example running up or down slopes and speed changes. However, when used in combination with the temperature measurements from the earpiece and possibly the heart rate measurements from the heart rate monitor, accuracy could quite possibly be increased. As an alternative to inserts, a pressure sensor could be integrated into a treadmill or other weight measurement mechanisms could be used.

Various embodiments may eventually be produced to cater for the various needs of:

- athletes (and novice sportsperson);
- 5 • military personnel;
- hospital patients and
- normal public users

For example, whilst athletes may be interested in actual numeric levels, the public
10 users may prefer an indicator in the form of a traffic light or similar (for example,
green = hydration normal, amber = a little dehydrated, red = very dehydrated).
Similarly, hospital patients themselves may not care about hydration levels - the
output data could be passed to medical staff for analysis and determination of
15 treatment or it may be fed into a control system for a fluid drip so that the fluid
intake for a patient could be automatically adjusted. Some embodiments may
include a memory and connection/transmission system so that data can be
recorded over time and uploaded onto a computer for more detailed analysis of
performance. An example embodiment of the present invention that may be used
20 by medical personnel or trainers of sportsmen is shown in Figure 4 in which the
wristwatch is replaced by a base station 100. As the base station need not be
portable, it can include a larger display 120 and/or more powerful speaker 110 and
a receiver having a greater reception radius to allow the subject to move further
from it and still be in contact. The base station could be used as well as a
25 wristwatch so both the sportsman and the trainer is able to see hydration levels -
indeed, they may even be provided different types of information depending on
their needs.

The device could also be used to prevent athletes reaching their 'ceiling
temperature' and having to stop running in, for example, an ultra endurance event
30 where the athlete is performing at their peak for several hours. An indication of
extreme temperature would allow the athlete to reduce their speed and continue
running instead of having to walk to cool down. This would apply even if there was
no water available. Therefore by using the device they don't lose valuable time,
and reduce the risk of damaging their body.

The device could also be used to determine cardiac changes in the body, particularly central blood volume, heart rate, stroke volume (these are relative to body water). This will help to prevent a reduction in cardiac output which will reduce the athletes performance, as described below:

- 10 In a preferred embodiment, the calculation used to determine hydration status may take account of fat percentage of body weight. This will address discrepancies in use where a subject has a large percentage of fat for body weight. Since fat contains little or no water, the device may not give accurate results for someone with a large percentage of fat content, as for that of a slender person (the slender person will no doubt have a greater percentage of water in their body than the fatter person).
- 15 Other factors that may be taken into account during the calculation may include the temperature of the surrounding environment. The magnitude of core temperature elevation can range from 0.1 to 0.23°C for every percent of body weight lost, and is greater during exercise in hot, as opposed to temperate climates.

CLAIMS

1. A hydration monitor comprising a temperature sensor for measuring a subject's core body temperature and a processor, the processor being arranged to
5 accept measurements from the temperature sensor and calculate a hydration level in dependence on changes in the measured core body temperature.
2. A hydration monitor as claimed in claim 1, comprising an earpiece and a remote unit, the temperature sensor being positioned in the earpiece for
10 measuring the core body temperature via the subject's tympanic membrane.
3. A hydration monitor as claimed in claim 2, wherein the temperature sensor comprises a thermopile.
- 15 4. A hydration monitor as claimed in claim 2 or 3, wherein the earpiece further comprises a transmitter, the remote unit including the processor, output means and a receiver, the earpiece being arranged to communicate measurements to the processor via the transmitter and receiver, the processor being arranged to provide an indication of the hydration level via the output means.
20
5. A hydration monitor as claimed in claim 4, wherein the transmitter and receiver communicate wirelessly.
6. A hydration monitor as claimed in claim 4 or 5, wherein the transmitter and
25 receiver are transceivers.
7. A hydration monitor as claimed in any of claims 4 to 6, wherein the remote unit comprises a selected one of:
a wristwatch, a personal digital organiser, a mobile telephone, a personal
30 computer or medical diagnostic and/or monitoring apparatus.
8. A hydration monitor as claimed in any of claims 4 to 7, wherein the output means includes one or more of a display and a speaker.

9. A hydration monitor as claimed in any preceding claim, further comprising a memory for storing hydration level and/or core body temperature over time.
10. A hydration monitor as claimed in any preceding claim, wherein the processor is arranged to determine a hydration level by the following formula:
5
$$\frac{[(\text{core body temperature current} - \text{core body temperature normal}) \times \text{subject's weight}]}{(\text{factor of ambient compensation} \times 100)}.$$
11. A hydration monitor as claimed in claim 10, wherein the factor of ambient compensation is between 0.1 and 0.23 and is determined in dependence on the temperature of the environment surrounding the subject.
12. A hydration monitor as claimed in any preceding claim arranged to operate repeatedly at predetermined time intervals.
13. A hydration monitor as claimed in any preceding claim, wherein the processor is arranged to generate an alarm upon determination of a hydration level below a predetermined level.
14. A method of measuring hydration of a subject comprising the steps of:
20 measuring an initial core body temperature of the subject;
measuring a subsequent current core body temperature of the subject;
subtracting the initial core body temperature from the subsequent core body temperature;
25 multiplying by the subject's weight; and,
dividing by a factor of ambient compensation.
15. A method as claimed in claim 14, wherein the measurements are taken from the subject's tympanic membrane.
16. A hydration monitor as herein described and as illustrated in the accompanying drawings.

17. A method as herein described and as illustrated in the accompanying drawings.

Abstract

HYDRATION MONITOR

- 5 A hydration monitor includes a temperature sensor (20; 65) for measuring a subject's core body temperature and a processor (30). The processor is arranged to accept measurements from the temperature sensor (20; 65) and calculate a hydration level in dependence on changes in the measured core body temperature.

10

[Fig. 2]